

Fristam FKL Positive Displacement Pump Specifications by Model

Model		15	20	25	50	75	150	205	250	400	580	600
Displacement (at max rpm)	gal/rev	0.0155	0.032	0.056	0.096	0.156	0.259	0.45	0.54	0.74	1.82	2.24
	gpm	15.5	25.6	33.6	57.6	93.6	155	270	324	444	728	896
	l/m	58.7	96.9	127.2	218	354	588	1022	1226	1681	2756	3392
	m ³ /hr	3.5	5.8	7.6	13.1	21.3	35.3	61.3	73	100	165	203
Speed (max)	rpm	1000	800	600	600	600	600	600	600	600	400	400
Pressure (max)	psi	200	200	300	500	500	500	500	500	500	300	300
	bar	14	14	21	35	35	35	35	35	35	21	21
Fittings												
Housing		1.5" clamp	1.5" clamp	1.5" clamp	2.5" clamp	2.5" clamp	3" clamp	4" clamp	4" clamp	6" flange	6" flange	6" flange
Seal Flush Thread		1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/8" NPT	M10 x 1.5
Weight (complete pump)	lbs	75	75	104	135	360	451	680	744	950	1580	1680
	kg	34	34	47	61	163	205	308	338	431	717	762
Special Options												
Rectangular Inlet		N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A
O-Ring Seal		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A	N/A